

C2 PS1

System Operation and Control

10199

Development and validation of new organisational models and systems for DER led restoration

C. SALTER¹, M. KENNY¹, D. NNABUIFE¹, P. CHANDLER¹,

D. GÜTSCHOW², D. CHAKRAVORTY²

¹National Grid ESO, ²TNEI services


Motivation

- As the GB electricity market becomes more decentralized, decarbonized and digitalized so the approach to Power System Restoration must change
- Work undertaken as part of the Distributed ReStart project developed organizational models, telecommunications requirements and control systems to enable resilient control of distributed energy resources under a system restoration scenario.

Method and Approach

- Extensive consultation with all organizations involved in GB restoration was used to baseline and identify risks
- Parallel development of technical requirements including telecommunication and cyber security capabilities was undertaken.
- Real world tests were conducted through desktop exercises, live network trials and system prototype real time digital simulation with hardware in the loop tests

Learn through application approach applied, including all organisations involved in restoration



Objects of investigation

- Create an end-to-end specification for the power systems, organisational, telecommunications, network code and procurement requirements to facilitate restoration from distributed assets
- Develop an organisational structure to facilitate the power systems findings and maximise the restoration speed whilst at minimum total cost to the end consumer
- Develop a functional specification for the control systems required to support the power systems and organisational capability gaps
- Define the functional telecommunications requirements for this process
- Demonstrate the effectiveness of the organisational designs through application using desktop exercises
- Demonstrate the effectiveness of the control system through real time digital simulation on a prototype

Experimental setup & test results

- A custom electricity simulator was developed enabling remote access to a common platform for DNOs, ESO, TO and DER. Feedback was collected to identify improvements and blockers in the process design
- 4 vendors were selected to develop a control system specification, the outputs of these were collated to create a functional specification from which a single vendor then developed the prototype for HiL testing

Discussion


- Organisational change will be needed to facilitate distributed restoration
- Local voltage and frequency management by distribution system operators is a very significant change but was accepted by all stakeholders
- No blockers were identified but multiple improvements were captured and incorporated into the final design.
- An online, interactive platform emulating control systems led to very high-quality improvements being identified and confidence in the processes developed
- Learnings from this development exercise can be applied to in-service training
- Engaging multiple vendors for an initial control system functional specification promoted competition, allowed for exploration of various conceptual design principles and led to overall improvements in the prototype build

Conclusion

- A working model for distribution level restoration has been developed and is being procured in GB as part of ongoing regional tenders
- Significant organizational, control system and power systems changes are needed to facilitate restoration from DER
- Changes identified and implemented from desktop exercises enabled significant refinement and development of the final organizational design
- Whilst these changes incur costs, the benefits of enhanced competition, decarbonisation and future proofing of an essential system capability leads to a net consumer benefit of between £86m and £144m
- Power engineering, control system and organizational challenges continue to exist in the models developed but ongoing training, assurance testing and infrastructure build will continuously refine the specifications

Development and validation of new organisational models and systems for DER led restoration Continued

Viability assessment



Roles and responsibilities

A central organisational model was developed:

- ESO continue to coordinate national restoration including instructing the start of plans
- DNOs lead locally and use a control system for management of real time frequency, voltage and generator dispatch



System operator

- Declare Black Start
- National strategy
- Regional strategy
- Instruct restoration zone start
- Instruct transmission restoration route
- Instruct power island growth



Transmission Owner

- Transmission network switching actions
- Data provision to DNO
- Co-develop transmission level strategy



Distributed Energy Resource

- Multiple individual providers deliver different services to the restoration zone
- Anchor DER provides the initial voltage and frequency source
- Top-up service providers support power island growth




Distribution Network Operator

- Declare and instruct restoration to service providers
- Develop local restoration strategy
- Distribution network switching actions
- Local voltage and frequency management


Restoration Zone

- The boundaries of responsibility for control system design and organisations are linked to a distribution restoration zone
- A distribution restoration zone is a combination of network, energy resources and demand which act as an effective restoration provider



Desktop Exercises


- A full end to end process based upon the Chapelcross restoration zone (left) and the organisational model (above) was conducted. A process map was developed
- This exercise included control engineers from all key organisations involved in the technical procedure and simulated an end-to-end restoration on an online platform




Development and validation of new organisational models and systems for DER led restoration Continued

Restoration Zone Control System


- Four different vendors were engaged to develop front end engineering designs for a control system
- A single vendor was then selected to build a prototype. The key functions and interactions with this selected design are detailed below
- Fast balancing functions maintain network stability through sub second control enhancing block load pickup capability of energy resources
- Slow balancing maintains appropriate energy distribution across the restoration process



- The communications and control architecture that facilitates these processes is summarized in the graphic below



Telecommunications interface map



Conclusions

A working model for distribution level restoration has been developed and is undergoing procurement in GB

- Cost benefit analysis has demonstrated expected consumer benefit of between £86m and £144m
- However, this model increases the complexity of restoration and leads to the following significant change requirements:



System operator

- Inter control centre protocol required for visibility between the DNOs and System Operator.
- Enhanced training requirements




Transmission Ownerpoints

- Phasor Measurement Units and data exchange with DNO to facilitate synchronisation
- Additional network synchronising



Distributed Energy Resource

- New power resilience and communications specification
- Technical changes to deliver contracted service
- Robust training and minimum staffing requirements



Distribution Network Operator

- Restoration control system implementation
- New power resilience and communications requirements
- Significantly enhanced training requirements
- Potential additional staff requirements